

F-450/750

Capital Radio is the only company in India having total in-house facility to manufacture all metal components of a loudspeaker, giving it an edge over all manufacturers in price, quality and flexibility to make speakers to customers specifications.

The range of speakers lies from 8" to 21" in spun steel and aluminum frames and also in ferrite or neodymium magnets.

Coil production is in-house in copper, aluminium and copper clad aluminium

SPECIFICATION


Power Rating	750W
Music Program	850W
Resonance	43 Hz
Frq. Range	55-3KHz
Sensitivity	97 dB
VC Dia	4"(102.8mm)

ELECTRO-MECHANICAL PARAMETERS

TARREST LAND	
DC Resistance	5.6 Ohm
Resonance Freq	43.361 Hz
S. Area Of Cone	141.863mM ²
Krm	42.533m Ohm
Erm	0.626
Kxm	61.277m H
Exm	0.579
Vas	234.768m M ³
Cms	82.151u M/N
Mmd	133.268 m Kg
Diaph. Mass	163.992 m Kg
(including	air load)
BI	20Tm
Mechanical Qms	4.425
Electromech, Qes	0.609
Total Qts	0.536
Efficiency	3.038%
SPL	97dB
Nom Basket Dia	18" 455mm
Nominal Impedance	8 Ohms



Impedance vs Freq



ADDITIONAL INFORMATION

Magnetic Materia	Sr+2 Ferrite mgt
Weight	2820g
MagDia Depth	220mm x 20mm
Mag. Assbly Wgt.	9320g
Core details	Vented & Extended
Frame Matrl	Spun&Stamped Mild stl
Frame finish	Black Matt
Voice Coil Mat.	Copper
Voice Coil Forme	r Polyimide
Cone Material	Non pressed long
	fiber pulp

Cone Edge Composition Cloth
Dust Cap Solid Composition paper

SHIPPING INFORMATION

Net Weight 12080gm Gross weight 14240gm BOX Dimension 460x460x210mm Cart Dimension

Cart Dimension